

Description

The LED Vapor Tight Fixtures are designed to save energy and meet low light egress requirements. Also the fixture is optimal for parking driver lane compliance.

For use s as utility lighting, parking garage and stairwell lighting where meets applicable buliding and safety codes.

Specification

| Item | Volt | Watt | CCT | LPW | Lumen |
|-------------------|----------|------|-------|-----|-------|
| VT-4/45/38/34/CCT | 120-277V | 45 | 3500K | 132 | 5940 |
| | | | 4000K | 133 | 5985 |
| | | | 5000K | 134 | 6030 |
| | | 38 | 3500K | 135 | 5130 |
| | | | 4000K | 136 | 5168 |
| | | | 5000K | 137 | 5206 |
| | | 34 | 3500K | 138 | 4692 |
| | | | 4000K | 139 | 4726 |
| | | | 5000K | 140 | 4760 |
| VT-8/90/75/65/CCT | 120-277V | 90 | 3500K | 132 | 11880 |
| | | | 4000K | 133 | 11970 |
| | | | 5000K | 134 | 12060 |
| | | 75 | 3500K | 135 | 10125 |
| | | | 4000K | 136 | 10200 |
| | | | 5000K | 137 | 10275 |
| | | 65 | 3500K | 138 | 8970 |
| | | | 4000K | 139 | 9035 |
| | | | 5000K | 140 | 9100 |

PERFORMANCE SUMMARY

Efficacy: 130LPW

Chip: Seoul 3528

CRI: Ra>80

CCT Options: 3500K 4000K 5000K

Driver: Dimmable LED power supplies

THD: <20%

PF: >0.9

The Driver ensures steady performance and long lifetime

Driver efficiency>85%.

Standard Lifetime: Designed minimum 50,000 Hours

Mounting: Fixture may be surface, pendant, or stem mounted

Standard Warranty: 5 Years

The Dimming type is continous, The product can dim to 10%

Suitable for Wet Location

Wired Communication Protocol: 0-10V



Dimension

| Item NO: | Lenth | Width | Depth |
|-----------------|-------|-------|-------|
| Vapor Tight-4FT | 47.2" | 3.5" | 3" |
| Vapor Tight-8FT | 94.5" | 3.5" | 3" |

Wiring Diagram

